

## Granville ATF MV

1 Litre, 5 Litre, 20 Litre & 205 Litre

### PRODUCT DESCRIPTION

Granville ATF-MV is a fully synthetic automatic transmission fluid manufactured by selecting the latest quality additives and base oils to formulate a truly outstanding product. ATF-MV meets and exceeds a wide range of specifications and approvals making this product suitable for multi-vehicle applications.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

GM: Dexron III H/M, Dexron II D/E, 9986195 & 93160393  
 Ford: Mercon&#174;, Mercon&#174; SP, Mercon&#174; V, WSS-M2C924-C, WSS-M2C202-B, WSS-M2C166-H & WSS-M2C195-A  
 Allison: C4  
 TES-295  
 MB: 236.3, 236.5, 236.6, 236.7 & 236.9  
 ZF: TE-ML-03D, TE-ML-04D, TE-ML-14B, TE-ML-16L & TE-ML-17C  
 VW: G 055 025-A2, G 052 162 & G 052 990-A2  
 Toyota: JWS3309, T-IV & WS  
 Mopar: ATF+3 & ATF+4 (7176)  
 Esso: LT71141ATF  
 Voith: G607  
 Texaco: 7045-E, ETL-8072B & N402  
 Volvo: 11 61 540-8  
 ATF: Type A, Suffix A (TASA), SPII & SPIII  
 Nissan: Matic J & Matic K  
 Saab: 93 165 147 & 3309  
 Honda: ATF-Z1  
 Shell: LA2634  
 Idemitsu: K17

### PRODUCT BENEFITS

- \* Fully synthetic
- \* Outstanding wear protection
- \* Multi-vehicle applications



\* Image for illustrative purposes only.

| SIZE             | PART NO | BARCODE       |
|------------------|---------|---------------|
| <b>1 Litre</b>   | 0004    | 5020618000044 |
| <b>5 Litre</b>   | 0005    | 5020618000051 |
| <b>20 Litre</b>  | 0086    | 5020618000860 |
| <b>205 Litre</b> | 0021    | 5020618000211 |



# Granville ATF MV

1 Litre, 5 Litre, 20 Litre & 205 Litre

## PRODUCT USAGE

Granville ATF-MV is designed for use in automatic transmissions where recommended also as a power steering fluid where recommended. For automatic transmissions where this specification lubricant is required.

## DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

|                   |                      |
|-------------------|----------------------|
| <b>Appearance</b> | : Red liquid         |
| <b>Odour</b>      | : Characteristic     |
| <b>Solubility</b> | : Insoluble in water |

| Test                       | Method    | Unit               | Min. | Max. | Typical |
|----------------------------|-----------|--------------------|------|------|---------|
| Viscosity, Kinematic 40°C  | ASTM D445 | mm <sup>2</sup> /s |      |      | 38.35   |
| Density                    | ASTM D792 | @ 15°C             |      |      | 0.848   |
| Viscosity, Kinematic 100°C | ASTM D445 | mm <sup>2</sup> /s |      |      | 7.291   |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

