

Granville Eplex 80/90

1 Litre, 5 Litre, 20 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville EPEX 80/90 is a multi-grade extreme pressure gear oil formulated for use in heavy duty, high load applications. The formulation provides a gear oil with outstanding anti wear protection. EPEX 80/90 is designed to cope with the increasing demands of modern day motoring which include high shock/load, high torque and high speeds.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5
MIL: MIL-L-2105 B, MIL-L-2105 C & MIL-L-2105 D
MAN: 342-Type M1 & 342-Type M2
Scania: STO 1.0
Volvo: 1273.10
ZF: TE-ML-05A, TE-ML-07A, TE-ML-08, TE-ML-12E, TE-ML-16B, TE-ML-16C, TE-ML-16D, TE-ML-17B, TE-ML-19B & TE-ML-21A

PRODUCT BENEFITS

- * Excellent high & low temperature performance
- * Outstanding protection against corrosion
- * Suitable for synchromesh gearboxes
- * Can be used where EP 80, EP 90 and GL4 specifications are also required

PRODUCT USAGE

For manual transmissions and axles where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0143	5020618001430
5 Litre	0173	5020618001737
20 Litre	0137	5020618001379
205 Litre	1486	5020618014867



Granville Epex 80/90

1 Litre, 5 Litre, 20 Litre & 205 Litre

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	13.5	<18.5	16.087
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			151.27
Density	ASTM D792	@ 15°C			0.8932

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

