

## Granville Two Stroke

500ml, 1 Litre, 5 Litre & 20 Litre

### PRODUCT DESCRIPTION

Granville Two Stroke is formulated for use in two stroke engines with oil injection or premix systems. The low ash, clean burn characteristics reduce carbon build up, prevent pre-ignition plug fouling and reduce smoke emissions. Two Stroke may also be used in garden machinery.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: TC  
JASO: FB

### PRODUCT BENEFITS

- \* Low ash formulation
- \* For oil injection or premix systems
- \* Low smoke formulation

### PRODUCT USAGE

For two stroke engines where this specification oil is recommended.

### DIRECTIONS FOR USE

As per the engine manufacturers recommendations.

### DOSAGE INFORMATION

Always check engine manufactures recommendations for mixing ratios.

### STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.



\* Image for illustrative purposes only.

| SIZE     | PART NO | BARCODE       |
|----------|---------|---------------|
| 500ml    | 0120    | 5020618001201 |
| 1 Litre  | 0118    | 5020618001188 |
| 5 Litre  | 0176    | 5020618001768 |
| 20 Litre | 0271    | 5020618002710 |



# Granville Two Stroke

500ml, 1 Litre, 5 Litre & 20 Litre

## SHELF LIFE

5 years from date of manufacture.

|                   |                      |
|-------------------|----------------------|
| <b>Appearance</b> | : Red liquid         |
| <b>Odour</b>      | : Characteristic     |
| <b>Solubility</b> | : Insoluble in water |

| Test                       | Method     | Unit               | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | 6.5  |      | 9.52    |
| Viscosity, Kinematic 40°C  | ASTM D445  | mm <sup>2</sup> /s |      |      | 72      |
| Density                    | ASTM D792  | @ 15°C             |      |      | 0.879   |
| Total Base Number          | ASTM D2896 | mg KOH/g           |      |      | 1.5     |
| Pour Point                 | ASTM D97   | °C                 |      |      | -21     |
| Viscosity Index            | ASTM D2270 |                    |      |      | 110     |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

