

## Granville Multi Hy-Vis 32

20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hypalube Multi Hy-vis 32 hydraulic oil is a high viscosity index fluid formulated for use in a wide range of agricultural, commercial and industrial applications where recommended, they offers excellent pumpability and protect against oxidation and corrosion.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

DIN: 51524 Part 2 (HLP), 51524 Part 3 (HVLP) & 51524 Part 1 (HL)

ISO: 11158 (HL, HM, HV)

AFNOR: NF ISO 11158 (HL, HM, HV)

Vickers: 1.286.S

US Steel: 126 & 127



\* Image for illustrative purposes only.

### PRODUCT BENEFITS

- \*High viscosity index
- \*Excellent pumpability
- \*Protect against oxidation and corrosion

### STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and keep out of the reach of children

### SHELF LIFE

5 years from date of manufacture

|                         |                      |
|-------------------------|----------------------|
| Appearance              | : Amber liquid       |
| Odour                   | : Characteristic     |
| Solubility              | : Insoluble in water |
| Percentage of Biodiesel | : Nil                |



# Granville Multi Hy-Vis 32

20 Litre & 199 Litre

| Test                      | Method    | Unit               | Min. | Max. | Typical |
|---------------------------|-----------|--------------------|------|------|---------|
| Viscosity, Kinematic 40°C | ASTM D445 | mm <sup>2</sup> /s | 28.8 | 35.2 |         |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

